

View Online at <https://aerobasegroup.com/nsn/5320-00-233-4781>

**Fastener Length:**

Between 0.115 inches and 0.135 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.061 inches and 0.065 inches

**Shank Style:**

Straight

**Head Major Diameter:**

Between 0.110 inches and 0.118 inches

**End Application:**

W/s: helicopter, mh-53e; helicopter, advance attack, ah-1w; missile, all-weather anti-ship, harpoon (agm-84); aircraft, (ac-130h, mc-130h, ec-130e, hc-130); aircraft, c-2a (reprocured); radar set, an/pps-5b; helicopter, carrier based asw, sh-60f; low altitude navigation & targeting infrared system (lantirn); communications systems an/wrr-7

**Grip Length:**

Between 0.021 inches and 0.041 inches

**Shear Strength:**

26000 single pounds per square inch

**Countersink Angle:**

Between 99.5 degrees and 100.5 degrees

**Material:**

Aluminum alloy 2117

**Material Specification:**

Qq-a-430 federal specification single material response

**Surface Treatment:**

Anodize or oxide film

**Surface Treatment Specification:**

Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0

**Mil-std (military Standard):**

Mil-a-8625 spec.