

View Online at <https://aerobasegroup.com/nsn/5320-00-233-4781>

Fastener Length:

Between 0.115 inches and 0.135 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.061 inches and 0.065 inches

Shank Style:

Straight

Head Major Diameter:

Between 0.110 inches and 0.118 inches

End Application:

W/s: helicopter, mh-53e; helicopter, advance attack, ah-1w; missile, all-weather anti-ship, harpoon (agm-84); aircraft, (ac-130h, mc-130h, ec-130e, hc-130); aircraft, c-2a (reprocured); radar set, an/pps-5b; helicopter, carrier based asw, sh-60f; low altitude navigation & targeting infrared system (lantirn); communications systems an/wrr-7

Grip Length:

Between 0.021 inches and 0.041 inches

Shear Strength:

26000 single pounds per square inch

Countersink Angle:

Between 99.5 degrees and 100.5 degrees

Material:

Aluminum alloy 2117

Material Specification:

Qq-a-430 federal specification single material response

Surface Treatment:

Anodize or oxide film

Surface Treatment Specification:

Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.