# NSN 5320-00-233-4811

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-233-4811

## Identification Code Color:

Yellow

# Fastener Length:

Between 1.115 inches and 1.135 inches

## Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

### Shank Diameter:

Between 0.124 inches and 0.128 inches

### Shank Style:

Straight w/radius chamfered tip

# Head Major Diameter:

Between 0.221 inches and 0.229 inches

## Grip Length:

0.927 mils and 0.947 centimeters

### Shear Strength:

41000 single pounds per square inch

## **Countersink Angle:**

Between 99.5 degrees and 100.5 degrees

## Heat Treatment:

T-73 solution heat treated

# Material:

Aluminum alloy 7050

### **Material Specification:**

Qq-a-430, t73 uns a97050 federal specification single material response

### Surface Treatment:

Oxide film

# Surface Treatment Specification:

Mil-c-5541, class 1a military specification single treatment response

# **Specification Data:**

96906-ms20426 government standard and 88044-an426/cancelled/ government standard

### Shelf Life:

N/a

# Unit Of Measure:

---

### Demilitarization:

No

Fiig:

A040a0

## Mil-std (military Standard):

Mil-c-5541 spec.