

View Online at <https://aerobasegroup.com/nsn/5320-00-233-4826>

**Fastener Length:**

Between 0.735 inches and 0.765 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.152 inches and 0.158 inches

**Shank Style:**

Straight

**Head Major Diameter:**

Between 0.272 inches and 0.293 inches

**Grip Length:**

0.516 inches

**Min. Tensile Strength (psi):**

43000 pounds per square inch

**Hardness Rating:**

60.0 rockwell b

**Shear Strength:**

32000 single pounds per square inch

**Countersink Angle:**

Between 88.0 degrees and 92.0 degrees

**Heat Treatment:**

Annealed

**Material:**

Steel comp 1008 or steel comp 1010

**Material Specification:**

Ase j430, grade 0, g10080 assn standard 1st material response or ams7225, g10100 assn standard 2nd material response

**Supplementary Features:**

Unplated plain gen purpose appl

**Specification Data:**

24617-135030 manufacturers standard and 81343-sae j492 professional/industrial association standard and 81348-ff-r-556 government standard

**Specification Or Standard:**

10 type and e grade

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0