

View Online at <https://aerobasegroup.com/nsn/5320-00-233-4826>

Fastener Length:

Between 0.735 inches and 0.765 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.152 inches and 0.158 inches

Shank Style:

Straight

Head Major Diameter:

Between 0.272 inches and 0.293 inches

Grip Length:

0.516 inches

Min. Tensile Strength (psi):

43000 pounds per square inch

Hardness Rating:

60.0 rockwell b

Shear Strength:

32000 single pounds per square inch

Countersink Angle:

Between 88.0 degrees and 92.0 degrees

Heat Treatment:

Annealed

Material:

Steel comp 1008 or steel comp 1010

Material Specification:

Ase j430, grade 0, g10080 assn standard 1st material response or ams7225, g10100 assn standard 2nd material response

Supplementary Features:

Unplated plain gen purpose appl

Specification Data:

24617-135030 manufacturers standard and 81343-sae j492 professional/industrial association standard and 81348-ff-r-556 government standard

Specification Or Standard:

10 type and e grade

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0