NSN 5320-00-233-4838

Solid Rivet - Page 1 of 1

A040a0



| View Online at https://aerobasegroup.com/nsn/5320-00-233-4838 |
|---------------------------------------------------------------------------------------------|
| Fastener Length: |
| Between 0.365 inches and 0.385 inches |
| Head Style: |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) |
| Shank Diameter: |
| Between 0.061 inches and 0.065 inches |
| Shank Style: |
| Straight w/radius chamfered tip |
| Head Major Diameter: |
| 0.090 inches |
| Grip Length: |
| 0.271 mils and 0.291 centimeters |
| Shear Strength: |
| 32000 single pounds per square inch |
| Countersink Angle: |
| Between 99.5 degrees and 101.5 degrees |
| Heat Treatment: |
| Annealed |
| Material: |
| Steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1013 or steel comp 1015 |
| Material Specification: |
| 66 federal standard all material responses |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq-p-416, type 2, class 3 federal specification all treatment responses |
| Specification Data: |
| 96906-ms20427 government standard and 88044-an427/canceled/ government standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |