

View Online at <https://aerobasegroup.com/nsn/5320-00-235-0377>

Fastener Length:

Between 1.115 inches and 1.135 inches

Head Style:

Err-090

Head Height:

Between 0.078 inches and 0.088 inches

Shank Diameter:

Between 0.372 inches and 0.374 inches

Shank Style:

Err-090

Head Major Diameter:

Between 0.565 inches and 0.600 inches

Grip Length:

Between 0.813 inches and 0.875 inches

Min. Tensile Strength (psi):

160000 pounds per square inch

Material:

Steel comp 4037 or steel comp 4130 or steel comp 4140 or steel comp 4340 or steel comp 8735 or steel comp 8740

Material Specification:

Mil-s-8695, g40370 military specification 1st material response or mil-s-6758, g41300 military specification 2nd material response or mil-s-5626 military specification 3rd material response or ams6382, g41400 assn standard 3rd material response or mil-s-5000, g43406 military specification 4th material response or mil-s-6098, g87350 military specification 5th material response or mil-s-6049 military specification 6th material response or ams6322, g87400 assn standard 6th material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification all treatment responses

Specification Data:

80205-nas1054 professional/industrial association standard and 80205-nas178/caanceled/ professional/industrial association standard and 73197-hs48 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-8695 spec.