## NSN 5320-00-235-1316

Pin-rivet - Page 1 of 1

A528u0

Mil-s-6098 spec.

Mil-std (military Standard):



View Online at https://aerobasegroup.com/nsn/5320-00-235-1316 **Head Style:** Err-090 **Head Height:** Between 0.045 inches and 0.055 inches Shank Diameter: 0.188 inches **Shank Style:** Err-090 **Head Major Diameter:** Between 0.295 inches and 0.315 inches **Grip Length:** 1.875 inches Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** 23.0 rockwell c Material: Steel comp 8735 or steel comp 8740 or steel comp 6150 or steel comp 4140 or steel comp e4340 or steel comp 4340 or steel comp 4037 or steel comp 4130 **Material Specification:** Mil-s-6098 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-5626 military specification 4th material response or mil-s-5000 military specification 5th material response or mil-s-5000 military specification 6th material response or ams 6300 assn standard 7th material response or mil-s-6758 military specification 8th material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification all treatment responses Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: