## NSN 5320-00-235-5857

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-235-5857 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.4580 inches and 1.4830 inches **Head Style:** Flush countersunk **Shank Diameter:** 0.3812 inches **Head Major Diameter:** Between 0.6310 inches and 0.6980 inches Tip Diameter: 0.3638 inches Lubrication: Cetyl alcohol **Grip Length:** Between 1.0520 inches and 1.0670 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.3125 inches **Shear Strength:** 108000 single pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp 8740 or steel comp e4340 **Material Specification:** Mil-s-6049 military specification 1st material response or mil-s-5000 military specification 2nd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5320-00-235-5857

Pin-rivet - Page 2 of 2



Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6049 spec.