NSN 5320-00-236-7244

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-236-7244

Between 0.865 inches and 0.885 inches Head Style: Universal Head Height: Between 0.067 inches and 0.077 inches Shank Diameter: Between 0.155 inches and 0.160 inches Shank Style: Straight Head Major Diameter: Between 0.296 inches and 0.328 inches Grip Length: Between 0.831 inches and 0.328 inches Grip Length: Between 0.831 inches and 0.651 inches Shear Strength: 26000 single pounds per square inch Material: Alluminum alloy 2117 Material Specification: Qq-a-430 federal specification single material response Surface Treatment: Anodize or oxide film Surface Treatment Specification: Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: A040a0 Mil-std (military Standard): Mil-a-8625 spec.	Fastener Length:
Universal Head Height: Between 0.067 inches and 0.077 inches Shank Diameter: Between 0.155 inches and 0.160 inches Shank Style: Straight Head Major Diameter: Between 0.296 inches and 0.328 inches Grip Length: Between 0.631 inches and 0.651 inches Shear Strength: 26000 single pounds per square inch Material: Aluminum alloy 2117 Material Specification: Qq-a-430 federal specification single material response Surface Treatment: Anodize or oxide film Surface Treatment Specification 1st treatment response or mil-c-5541 military specification 2nd treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fitg: A040a0 Mil-std (military Standard):	Between 0.865 inches and 0.885 inches
Head Height: Between 0.067 inches and 0.077 inches Shank Diameter: Between 0.155 inches and 0.160 inches Shank Style: Straight Head Major Diameter: Between 0.296 inches and 0.328 inches Grip Length: Between 0.631 inches and 0.651 inches Shear Strength: Between 0.631 inches and 0.651 inches Shear Strength: 26000 single pounds per square inch Material: Aluminum alloy 2117 Material Specification: Qq-a-430 federal specification single material response Surface Treatment: Anodize or oxide film Surface Treatment Specification 1st treatment response or mil-c-5541 military specification 2nd treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig: A040a0 Mil-std (military Standard):	Head Style:
Between 0.067 inches and 0.077 inches Shank Diameter: Between 0.155 inches and 0.160 inches Shank Style: Straight Head Major Diameter: Between 0.296 inches and 0.328 inches Grip Length: Between 0.631 inches and 0.651 inches Shear Strength: 26000 single pounds per square inch Material: Aluminum alloy 2117 Material Specification: Qq-a-430 federal specification single material response Surface Treatment: Anodize or oxide film Surface Treatment Specification 1st treatment response or mil-c-5541 military specification 2nd treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig: A040a0 Mil-std (military Standard):	Universal
Shank Diameter: Between 0.155 inches and 0.160 inches Shank Style: Straight Head Major Diameter: Between 0.296 inches and 0.328 inches Grip Length: Between 0.631 inches and 0.651 inches Shear Strength: 26000 single pounds per square inch Material: Aluminum alloy 2117 Material Specification: Qq-a-430 federal specification single material response Surface Treatment: Anodize or oxide film Surface Treatment Specification 1st treatment response or mil-c-5541 military specification 2nd treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A040a0 Mil-std (military Standard):	Head Height:
Between 0.155 inches and 0.160 inches Shank Style: Straight Head Major Diameter: Between 0.296 inches and 0.328 inches Grip Length: Between 0.631 inches and 0.651 inches Shear Strength: 26000 single pounds per square inch Material: Aluminum alloy 2117 Material Specification: Qq-a-430 federal specification single material response Surface Treatment: Anodize or oxide film Surface Treatment Specification 1st treatment response or mil-c-5541 military specification 2nd treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A040a0 Mil-std (military Standard):	Between 0.067 inches and 0.077 inches
Shank Style: Straight Head Major Diameter: Between 0.296 inches and 0.328 inches Grip Length: Between 0.631 inches and 0.651 inches Shear Strength: 26000 single pounds per square inch Material: Aluminum alloy 2117 Material Specification: Qq-a-430 federal specification single material response Surface Treatment: Anodize or oxide film Surface Treatment Specification 1st treatment response or mil-c-5541 military specification 2nd treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: A040a0 Mil-std (military Standard):	Shank Diameter:
Straight Head Major Diameter: Between 0.296 inches and 0.328 inches Grip Length: Between 0.631 inches and 0.651 inches Shear Strength: 26000 single pounds per square inch Material: Aluminum alloy 2117 Material Specification: Qq-a-430 federal specification single material response Surface Treatment: Anodize or oxide film Surface Treatment Specification: Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fitig: A040a0 Mil-std (military Standard):	Between 0.155 inches and 0.160 inches
Head Major Diameter: Between 0.296 inches and 0.328 inches Grip Length: Between 0.631 inches and 0.651 inches Shear Strength: 26000 single pounds per square inch Material: Aluminum alloy 2117 Material Specification: Qq-a-430 federal specification single material response Surface Treatment: Anodize or oxide film Surface Treatment Specification 1st treatment response or mil-c-5541 military specification 2nd treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A040a0 Mil-std (military Standard):	Shank Style:
Between 0.296 inches and 0.328 inches Grip Length: Between 0.631 inches and 0.651 inches Shear Strength: 26000 single pounds per square inch Material: Aluminum alloy 2117 Material Specification: Qq-a-430 federal specification single material response Surface Treatment: Anodize or oxide film Surface Treatment Specification 1st treatment response or mil-c-5541 military specification 2nd treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A040a0 Mil-std (military Standard):	Straight
Grip Length: Between 0.631 inches and 0.651 inches Shear Strength: 26000 single pounds per square inch Material: Aluminum alloy 2117 Material Specification: Qq-a-430 federal specification single material response Surface Treatment: Anodize or oxide film Surface Treatment Specification: Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A040a0 Mil-std (military Standard):	Head Major Diameter:
Between 0.631 inches and 0.651 inches Shear Strength: 26000 single pounds per square inch Material: Aluminum alloy 2117 Material Specification: Qq-a-430 federal specification single material response Surface Treatment: Anodize or oxide film Surface Treatment Specification 1st treatment response or mil-c-5541 military specification 2nd treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A040a0 Mil-std (military Standard):	Between 0.296 inches and 0.328 inches
Shear Strength: 26000 single pounds per square inch Material: Aluminum alloy 2117 Material Specification: Qq-a-430 federal specification single material response Surface Treatment: Anodize or oxide film Surface Treatment Specification: Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A040a0 Mil-std (military Standard):	Grip Length:
26000 single pounds per square inch Material: Aluminum alloy 2117 Material Specification: Qq-a-430 federal specification single material response Surface Treatment: Anodize or oxide film Surface Treatment Specification: Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A040a0 Mil-std (military Standard):	Between 0.631 inches and 0.651 inches
Material: Aluminum alloy 2117 Material Specification: Qq-a-430 federal specification single material response Surface Treatment: Anodize or oxide film Surface Treatment Specification: Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A040a0 Mil-std (military Standard):	Shear Strength:
Aluminum alloy 2117 Material Specification: Qq-a-430 federal specification single material response Surface Treatment: Anodize or oxide film Surface Treatment Specification: Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A040a0 Mil-std (military Standard):	26000 single pounds per square inch
Material Specification: Qq-a-430 federal specification single material response Surface Treatment: Anodize or oxide film Surface Treatment Specification: Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A040a0 Mil-std (military Standard):	Material:
Qq-a-430 federal specification single material response Surface Treatment: Anodize or oxide film Surface Treatment Specification: Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A040a0 Mil-std (military Standard):	Aluminum alloy 2117
Surface Treatment: Anodize or oxide film Surface Treatment Specification: Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A040a0 Mil-std (military Standard):	Material Specification:
Anodize or oxide film Surface Treatment Specification: Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A040a0 Mil-std (military Standard):	Qq-a-430 federal specification single material response
Surface Treatment Specification: Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A040a0 Mil-std (military Standard):	Surface Treatment:
Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A040a0 Mil-std (military Standard):	Anodize or oxide film
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A040a0 Mil-std (military Standard):	Surface Treatment Specification:
N/a Unit Of Measure: Demilitarization: No Fiig: A040a0 Mil-std (military Standard):	Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response
Unit Of Measure: Demilitarization: No Fiig: A040a0 Mil-std (military Standard):	Shelf Life:
Demilitarization: No Fiig: A040a0 Mil-std (military Standard):	N/a
No Fiig: A040a0 Mil-std (military Standard):	Unit Of Measure:
No Fiig: A040a0 Mil-std (military Standard):	
Fiig: A040a0 Mil-std (military Standard):	Demilitarization:
A040a0 Mil-std (military Standard):	No
Mil-std (military Standard):	Fiig:
	A040a0
Mil-a-8625 spec.	Mil-std (military Standard):
	Mil-a-8625 spec.