

View Online at <https://aerobasegroup.com/nsn/5320-00-237-8136>

**Fastener Length:**

1.006 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.274 inches and 0.276 inches

**Shank Style:**

Threaded self-plugging shank w/sleeve

**Head Major Diameter:**

Between 0.499 inches and 0.507 inches

**Expansion Device:**

Threaded stem

**Grip Length:**

Between 0.845 inches and 0.906 inches

**Hardness Rating:**

39.0 rockwell c and 43.0 rockwell c

**Shear Strength:**

9300 double pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Special Features:**

Self-locking

**Heat Treatment:**

Annealed

**Material:**

Steel comp 8740 stem

**Material Specification:**

Mil-s-6049 military specification single material response stem

**Surface Treatment:**

Cadmium stem

**Surface Treatment Specification:**

Qq-p-416, type 1, cl 3 federal specification single treatment response sleeve

**Specification Data:**

80205-nas1750 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0

**Mil-std (military Standard):**

Mil-s-6049 spec.