

View Online at <https://aerobasegroup.com/nsn/5320-00-239-1293>

Fastener Length:

Between 0.287 inches and 0.307 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.125 inches and 0.129 inches

Shank Style:

Self-plugging shank w/grooved end for locking

Head Major Diameter:

Between 0.207 inches and 0.225 inches

Expansion Device:

Serrated stem-type w

End Application:

W/s: helicopter, carrier based asw, sh-60f; tactical air opns module (an/tyq (23); fms-aircraft, hawkeye e-2c; helicopter, uscg search and rescue, hh-60j; fms-a7 aircraft; aircraft, (ac-130h, mc-130h, ec-130e, hc-130) ; helicopter, search and rescue, hh-60h; joint stars target radar system; helicopter, seahawk, h-60; helicopter, mh-53e

Grip Length:

Between 0.179 inches and 0.203 inches

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Aluminum alloy 5056 sleeve

Material Specification:

Qq-a-430 federal specification single material response stem

Surface Treatment:

Anodize stem or chromate stem

Surface Treatment Specification:

Mil-a-8625 military specification 1st treatment response stem or mil-c-5541 military specification 2nd treatment response stem

Specification Data:

80205-nas1921 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.