NSN 5320-00-241-5902

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-241-5902

Between 1.240 inches and 1.260 inches Head Style: Universal Head Height: Between 0.161 inches and 0.171 inches Shank Diameter: Between 0.374 inches and 0.379 inches Shank Style: Straight Head Major Diameter: Between 0.713 inches and 0.787 inches Grip Length: Between 0.678 inches and 0.698 inches Shear Strength: 26000 single pounds per square inch Material: Aluminum alloy 2117 Material Specification: Qq-a-430 federal specification single material response Surface Treatment: Oxide film or anodize Surface Treatment Specification: Mil-c-5541 military specification 1st treatment response or mil-a-8625 military specification 2nd treatment respons Sheft Life: N/a Unit Of Measure: Demilitarization: No Flig: A040a0	astener Length:
Universal Head Height: Between 0.161 inches and 0.171 inches Shank Diameter: Between 0.374 inches and 0.379 inches Shank Style: Straight Head Major Diameter: Between 0.713 inches and 0.787 inches Grip Length: Between 0.713 inches and 0.787 inches Grip Length: Between 0.678 inches and 0.698 inches Shear Strength: 26000 single pounds per square inch Material: Aluminum alloy 2117 Material Specification: Qq-a-430 federal specification single material response Surface Treatment: Oxide film or anodize Surface Treatment Specification: Mil-c-5541 military specification 1st treatment response or mil-a-8625 military specification 2nd treatment respons Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	etween 1.240 inches and 1.260 inches
Head Height: Between 0.161 inches and 0.171 inches Shank Diameter: Between 0.374 inches and 0.379 inches Shank Style: Straight Head Major Diameter: Between 0.713 inches and 0.787 inches Grip Length: Between 0.678 inches and 0.698 inches Shear Strength: 26000 single pounds per square inch Material: Aluminum alloy 2117 Material Specification: Qq-a-430 federal specification single material response Surface Treatment: Oxide film or anodize Surface Treatment Specification 1st treatment response or mil-a-8625 military specification 2nd treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	ead Style:
Between 0.161 inches and 0.171 inches Shank Diameter: Between 0.374 inches and 0.379 inches Shank Style: Straight Head Major Diameter: Between 0.713 inches and 0.787 inches Grip Length: Between 0.678 inches and 0.698 inches Shear Strength: 26000 single pounds per square inch Material: Aluminum alloy 2117 Material Specification: Qq-a-430 federal specification single material response Surface Treatment: Oxide film or anodize Surface Treatment Specification 1st treatment response or mil-a-8625 military specification 2nd treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	niversal
Shank Diameter: Between 0.374 inches and 0.379 inches Shank Style: Straight Head Major Diameter: Between 0.713 inches and 0.787 inches Grip Length: Between 0.678 inches and 0.698 inches Shear Strength: 26000 single pounds per square inch Material: Aluminum alloy 2117 Material Specification: Qq-a-430 federal specification single material response Surface Treatment: Oxide film or anodize Surface Treatment Specification 1st treatment response or mil-a-8625 military specification 2nd treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	ead Height:
Between 0.374 inches and 0.379 inches Shank Style: Straight Head Major Diameter: Between 0.713 inches and 0.787 inches Grip Length: Between 0.678 inches and 0.698 inches Shear Strength: 26000 single pounds per square inch Material: Aluminum alloy 2117 Material Specification: Qq-a-430 federal specification single material response Surface Treatment: Oxide film or anodize Surface Treatment Specification: Mili-c-5541 military specification 1st treatment response or mil-a-8625 military specification 2nd treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	etween 0.161 inches and 0.171 inches
Shank Style: Straight Head Major Diameter: Between 0.713 inches and 0.787 inches Grip Length: Between 0.678 inches and 0.698 inches Shear Strength: 26000 single pounds per square inch Material: Aluminum alloy 2117 Material Specification: Qq-a-430 federal specification single material response Surface Treatment: Oxide film or anodize Surface Treatment Specification: Mil-c-5541 military specification 1st treatment response or mil-a-8625 military specification 2nd treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fitig:	hank Diameter:
Straight Head Major Diameter: Between 0.713 inches and 0.787 inches Grip Length: Between 0.678 inches and 0.698 inches Shear Strength: 26000 single pounds per square inch Material: Aluminum alloy 2117 Material Specification: Qq-a-430 federal specification single material response Surface Treatment: Oxide film or anodize Surface Treatment Specification 1st treatment response or mil-a-8625 military specification 2nd treatment respons Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	etween 0.374 inches and 0.379 inches
Head Major Diameter: Between 0.713 inches and 0.787 inches Grip Length: Between 0.678 inches and 0.698 inches Shear Strength: 26000 single pounds per square inch Material: Aluminum alloy 2117 Material Specification: Qq-a-430 federal specification single material response Surface Treatment: Oxide film or anodize Surface Treatment Specification: Mil-c-5541 military specification 1st treatment response or mil-a-8625 military specification 2nd treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	hank Style:
Between 0.713 inches and 0.787 inches Grip Length: Between 0.678 inches and 0.698 inches Shear Strength: 26000 single pounds per square inch Material: Aluminum alloy 2117 Material Specification: Qq-a-430 federal specification single material response Surface Treatment: Oxide film or anodize Surface Treatment Specification: Mil-c-5541 military specification 1st treatment response or mil-a-8625 military specification 2nd treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	traight
Grip Length: Between 0.678 inches and 0.698 inches Shear Strength: 26000 single pounds per square inch Material: Aluminum alloy 2117 Material Specification: Qq-a-430 federal specification single material response Surface Treatment: Oxide film or anodize Surface Treatment Specification: Mil-c-5541 military specification 1st treatment response or mil-a-8625 military specification 2nd treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	ead Major Diameter:
Between 0.678 inches and 0.698 inches Shear Strength: 26000 single pounds per square inch Material: Aluminum alloy 2117 Material Specification: Qq-a-430 federal specification single material response Surface Treatment: Oxide film or anodize Surface Treatment Specification: Mil-c-5541 military specification 1st treatment response or mil-a-8625 military specification 2nd treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	etween 0.713 inches and 0.787 inches
Shear Strength: 26000 single pounds per square inch Material: Aluminum alloy 2117 Material Specification: Qq-a-430 federal specification single material response Surface Treatment: Oxide film or anodize Surface Treatment Specification: Mil-c-5541 military specification 1st treatment response or mil-a-8625 military specification 2nd treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	rip Length:
26000 single pounds per square inch Material: Aluminum alloy 2117 Material Specification: Qq-a-430 federal specification single material response Surface Treatment: Oxide film or anodize Surface Treatment Specification: Mil-c-5541 military specification 1st treatment response or mil-a-8625 military specification 2nd treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	etween 0.678 inches and 0.698 inches
Material: Aluminum alloy 2117 Material Specification: Qq-a-430 federal specification single material response Surface Treatment: Oxide film or anodize Surface Treatment Specification: Mil-c-5541 military specification 1st treatment response or mil-a-8625 military specification 2nd treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	hear Strength:
Aluminum alloy 2117 Material Specification: Qq-a-430 federal specification single material response Surface Treatment: Oxide film or anodize Surface Treatment Specification: Mil-c-5541 military specification 1st treatment response or mil-a-8625 military specification 2nd treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	3000 single pounds per square inch
Material Specification: Qq-a-430 federal specification single material response Surface Treatment: Oxide film or anodize Surface Treatment Specification: Mil-c-5541 military specification 1st treatment response or mil-a-8625 military specification 2nd treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	aterial:
Qq-a-430 federal specification single material response Surface Treatment: Oxide film or anodize Surface Treatment Specification: Mil-c-5541 military specification 1st treatment response or mil-a-8625 military specification 2nd treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	uminum alloy 2117
Surface Treatment: Oxide film or anodize Surface Treatment Specification: Mil-c-5541 military specification 1st treatment response or mil-a-8625 military specification 2nd treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	aterial Specification:
Oxide film or anodize Surface Treatment Specification: Mil-c-5541 military specification 1st treatment response or mil-a-8625 military specification 2nd treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	q-a-430 federal specification single material response
Surface Treatment Specification: Mil-c-5541 military specification 1st treatment response or mil-a-8625 military specification 2nd treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	urface Treatment:
Mil-c-5541 military specification 1st treatment response or mil-a-8625 military specification 2nd treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	xide film or anodize
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	urface Treatment Specification:
N/a Unit Of Measure: Demilitarization: No Fiig:	il-c-5541 military specification 1st treatment response or mil-a-8625 military specification 2nd treatment response
Unit Of Measure: Demilitarization: No Fiig:	helf Life:
Demilitarization: No Fiig:	/a
No Fiig:	nit Of Measure:
No Fiig:	
Fiig:	emilitarization:
-	0
A040a0	ig:
	040a0
Mil-std (military Standard):	il-std (military Standard):
Mil-c-5541 spec.	il-c-5541 spec.