## NSN 5320-00-242-7941

Blind Rivet - Page 1 of 1

Mil-s-6049 spec.



View Online at https://aerobasegroup.com/nsn/5320-00-242-7941

Fastener Length:
1.069 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.274 inches and 0.276 inches
Shank Style:
Threaded self-plugging shank w/sleeve
Head Major Diameter:
Between 0.499 inches and 0.507 inches
Expansion Device:
Threaded stem
Grip Length:
Between 0.907 inches and 0.969 inches
Hardness Rating:
39.0 rockwell c and 43.0 rockwell c
Shear Strength:
9300 double pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Special Features:
Self-locking
Material:
Steel comp 8740 stem
Material Specification:
Mil-s-6049 military specification single material response stem
Surface Treatment:
Cadmium stem
Surface Treatment Specification:
Qq-p-416, type 1, cl 3 federal specification single treatment response sleeve
Specification Data:
80205-nas1750 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A040a0
Mil-std (military Standard):