NSN 5320-00-243-3870

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-243-3870

Identification Code Color:

Yellow

Fastener Length:

Between 1.365 inches and 1.385 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.124 inches and 0.128 inches

Shank Style:

Straight w/radius chamfered tip

Head Major Diameter:

Between 0.221 inches and 0.229 inches

Grip Length:

1.178 mils and 1.198 centimeters

Shear Strength:

41000 single pounds per square inch

Countersink Angle:

Between 99.5 degrees and 100.5 degrees

Heat Treatment:

T-73 solution heat treated

Material:

Aluminum alloy 7050

Material Specification:

Qq-a-430, t73 uns a97050 federal specification single material response

Surface Treatment:

Oxide film

Surface Treatment Specification:

Mil-c-5541, class 1a military specification single treatment response

Specification Data:

96906-ms20426 government standard and 88044-an426/canceled/ government standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-c-5541 spec.