NSN 5320-00-243-3922

Solid Rivet - Page 1 of 1



view Online at https://aerobasegroup.com/nsn/5520-00-245-3922
Identification Code Color:
Yellow
Fastener Length:
Between 0.740 inches and 0.760 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.374 inches and 0.378 inches
Shank Style:
Straight w/radius chamfered tip
Head Major Diameter:
Between 0.690 inches and 0.698 inches
Grip Length:
0.178 mils and 0.198 centimeters
Shear Strength:
41000 single pounds per square inch
Countersink Angle:
Between 99.5 degrees and 100.5 degrees
Heat Treatment:
T-73 solution heat treated
Material:
Aluminum alloy 7050
Material Specification:
Qq-a-430, t73 uns a97050 federal specification single material response
Surface Treatment:
Oxide film
Surface Treatment Specification:
Mil-c-5541, class 1a military specification single treatment response
Specification Data:
96906-ms20426 government standard and 88044-an426/canceled/ government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A040a0
Mil-std (military Standard):
NAT - 5544

Mil-c-5541 spec.