NSN 5320-00-243-8361

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-243-8361

Between 0.615 inches and 0.635 inches Head Style: Universal Head Height: Between 0.027 inches and 0.037 inches Shank Diameter: Between 0.061 inches and 0.065 inches Shank Style: Straight Head Major Diameter: Between 0.119 inches and 0.131 inches Grip Length: Between 0.521 inches and 0.541 inches
Universal Head Height: Between 0.027 inches and 0.037 inches Shank Diameter: Between 0.061 inches and 0.065 inches Shank Style: Straight Head Major Diameter: Between 0.119 inches and 0.131 inches Grip Length:
Head Height: Between 0.027 inches and 0.037 inches Shank Diameter: Between 0.061 inches and 0.065 inches Shank Style: Straight Head Major Diameter: Between 0.119 inches and 0.131 inches Grip Length:
Between 0.027 inches and 0.037 inches Shank Diameter: Between 0.061 inches and 0.065 inches Shank Style: Straight Head Major Diameter: Between 0.119 inches and 0.131 inches Grip Length:
Shank Diameter: Between 0.061 inches and 0.065 inches Shank Style: Straight Head Major Diameter: Between 0.119 inches and 0.131 inches Grip Length:
Between 0.061 inches and 0.065 inches Shank Style: Straight Head Major Diameter: Between 0.119 inches and 0.131 inches Grip Length:
Shank Style: Straight Head Major Diameter: Between 0.119 inches and 0.131 inches Grip Length:
Straight Head Major Diameter: Between 0.119 inches and 0.131 inches Grip Length:
Head Major Diameter: Between 0.119 inches and 0.131 inches Grip Length:
Between 0.119 inches and 0.131 inches Grip Length:
Grip Length:
Between 0.521 inches and 0.541 inches
Shear Strength:
26000 single pounds per square inch
Material:
Aluminum alloy 2117
Material Specification:
Qq-a-430 federal specification single material response
Surface Treatment:
Anodize or oxide film
Surface Treatment Specification:
Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A040a0
Mil-std (military Standard):
Mil-a-8625 spec.