

View Online at <https://aerobasegroup.com/nsn/5320-00-245-3958>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.082 inches and 1.102 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.079 inches and 0.080 inches

Shank Diameter:

Between 0.163 inches and 0.164 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.220 inches and 0.258 inches

Grip Length:

0.817 inches

Min. Tensile Strength (psi):

260000 pounds per square inch

Hardness Rating:

50.0 rockwell c and 55.0 rockwell c

Thread Size:

0.164 inches

Shear Strength:

6400 double pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Special Features:

Single shear strength 156000

Material:

Steel comp h11

Material Specification:

Ams 6485 assn standard single material response

Surface Treatment:

Cadmium or nickel and cadmium

Surface Treatment Specification:

Mil-c-8837, type 2, cl 2 military specification 1st treatment response or ams 2416 assn standard 2nd treatment response or ams 2416 assn standard 3rd treatment response

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-c-8837 spec.