NSN 5320-00-246-0374

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-246-0374 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.753 inches and 0.773 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.079 inches and 0.081 inches **Shank Diameter:** Between 0.189 inches and 0.190 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.349 inches and 0.354 inches **Grip Length:** 0.443 inches **Thread Size:** 0.190 inches **Countersink Angle:** 100.0 degrees **Heat Treatment:** T-6 solution heat treated Material: Aluminum alloy 7075 **Material Specification:** Qq-a-225/9 federal specification single material response or qq-a-430 federal specification single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625 military specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig:

. -

A528u0

NSN 5320-00-246-0374

Pin-rivet - Page 2 of 2



Mil-std (military Standard):

Mil-a-8625 spec.