

View Online at <https://aerobasegroup.com/nsn/5320-00-246-0375>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.690 inches and 0.710 inches

Head Style:

Err-090

Head Height:

Between 0.055 inches and 0.065 inches

Width Between Flats:

Between 0.079 inches and 0.081 inches

Shank Diameter:

Between 0.189 inches and 0.190 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.295 inches and 0.315 inches

End Application:

W/s: deep submergence systems programs (dssp); ah-64-d longbow; helicopter, seahawk h-60; aircraft, viking s-3b; helicopter, apache ah-64; aircraft, stratolifter c-135; aircraft, hercules c-130; helicopter, rh-53; aircraft, galaxy c-5; aircraft, airlifter c-17a

Grip Length:

0.380 inches

Thread Size:

0.190 inches

Heat Treatment:

T-6 solution heat treated

Material:

Aluminum alloy 7075

Material Specification:

Qq-a-225/9 federal specification single material response or qq-a-430 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-a-8625 spec.