NSN 5320-00-251-8368

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-251-8368

Fastener Length:

Between 1.615 inches and 1.635 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Head Height:

0.055 inches

Shank Diameter:

Between 0.155 inches and 0.159 inches

Shank Style:

Straight with tapered tip

Head Major Diameter:

Between 0.282 inches and 0.290 inches

Chamfer Length:

0.039 inches

Tip Diameter:

0.078 inches

Grip Length:

Between 1.381 inches and 1.401 inches

Shear Strength:

26000 single pounds per square inch

Countersink Angle:

Between 99.5 degrees and 100.5 degrees

Heat Treatment:

T-4 solution heat treated

Material:

Aluminum alloy 2117

Material Specification:

Qq-a-430 federal specification single material response

Surface Treatment:

Anodize or oxide film

Surface Treatment Specification:

Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response

```
Shelf Life:
```

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.