

View Online at <https://aerobasegroup.com/nsn/5320-00-253-2326>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.246 inches and 1.271 inches

**Head Style:**

Err-090

**Head Height:**

0.070 inches

**Shank Diameter:**

0.2864 inches

**Shank Style:**

Pin-riquet, tapered, threaded

**Head Major Diameter:**

0.440 inches

**Tip Diameter:**

0.2864 inches

**Lubrication:**

Cetyl alcohol

**End Application:**

W/s: aircraft, stratofortress b-52; aircraft, starlifter c-141

**Grip Length:**

Between 0.865 inches and 0.880 inches

**Thread Size:**

0.250 inches

**Shear Strength:**

108000 single pounds per square inch

**Material:**

Steel comp e4340 or steel comp 4340 or steel comp 8740

**Material Specification:**

Mil-s-5000 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-5000 spec.