## NSN 5320-00-253-4188

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-253-4188

view Offiline at https://derobasegroup.com/fish/0020-00-200
Fastener Length:
Between 0.745 inches and 0.755 inches
Head Style:
Undersized oval countersunk
Head Height:
Between 0.004 inches and 0.006 inches
Shank Diameter:
Between 0.249 inches and 0.252 inches
Shank Style:
Straight
Head Major Diameter:
Between 0.376 inches and 0.396 inches
Head Minor Diameter:
Between 0.316 inches and 0.326 inches
Countersink Height:
0.062 inches
Shear Strength:
3240 double pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Special Features:
Single shear strength 33000
Heat Treatment:
T-4 solution heat treated
Material:
Aluminum alloy 2017
Material Specification:
Qq-a-430 federal specification single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-c-5541 military specification single treatment response
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

Mil-std (military Standard): Mil-c-5541 spec.

A040a0