NSN 5320-00-253-4190

Solid Rivet - Page 1 of 1



90

| View Online at https://aerobasegroup.com/nsn/5320-00-253-41 |
|---|
| Fastener Length: |
| Between 0.495 inches and 0.505 inches |
| Head Style: |
| Undersized oval countersunk |
| Head Height: |
| Between 0.004 inches and 0.006 inches |
| Shank Diameter: |
| Between 0.249 inches and 0.252 inches |
| Shank Style: |
| Straight |
| Head Major Diameter: |
| Between 0.376 inches and 0.396 inches |
| Head Minor Diameter: |
| Between 0.316 inches and 0.326 inches |
| Countersink Height: |
| 0.062 inches |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Heat Treatment: |
| T-4 solution heat treated |
| Material: |
| Aluminum alloy 2017 |
| Material Specification: |
| Qq-a-430 federal specification single material response |
| Surface Treatment: |
| Anodize |
| Surface Treatment Specification: |
| Mil-c-5541 military specification single treatment response |
| Specification Data: |
| 18205-bacr15ce manufacturers standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A040a0 |
| Mil-std (military Standard): |

Mil-c-5541 spec.