

View Online at <https://aerobasegroup.com/nsn/5320-00-256-8836>

**Fastener Length:**

Between 0.428 inches and 0.448 inches

**Head Style:**

Undersized oval countersunk

**Head Height:**

Between 0.003 inches and 0.005 inches

**Shank Diameter:**

Between 0.155 inches and 0.158 inches

**Shank Style:**

Straight

**Head Major Diameter:**

Between 0.2251 inches and 0.2469 inches

**Head Minor Diameter:**

Between 0.185 inches and 0.195 inches

**Countersink Height:**

0.0372 inches

**Grip Length:**

Between 0.194 inches and 0.214 inches

**Shear Strength:**

24000 single pounds per square inch

**Countersink Angle:**

Between 99.5 degrees and 100.5 degrees

**Heat Treatment:**

H-32 strain hardened

**Material:**

Aluminum alloy 5056

**Material Specification:**

Qq-a-430 federal specification single material response

**Surface Treatment:**

Anodize or oxide film

**Surface Treatment Specification:**

Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response

**Specification Data:**

80205-nas1097 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0

**Mil-std (military Standard):**

Mil-a-8625 spec.