NSN 5320-00-262-7802

Pin-rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-262-7802

Fastener Length:
Between 1.571 inches and 1.591 inches
Head Style:
Err-090
Head Height:
Between 0.068 inches and 0.078 inches
Shank Diameter:
Between 0.310 inches and 0.312 inches
Shank Style:
Err-090
Head Major Diameter:
Between 0.475 inches and 0.505 inches
Grip Length:
Between 1.313 inches and 1.375 inches
Min. Tensile Strength (psi):
160000 pounds per square inch
Material:
Steel comp 4037 or steel comp 4130 or steel comp 4140 or steel comp 4340 or steel comp 8735 or steel comp 8740
Material Specification:
Mil-s-8695, g40370 military specification 1st material response or mil-s-6758, g41300 military specification 2nd material response or
mil-s-5626 military specification 3rd material response or ams6382, g41400 assn standard 3rd material response or mil-s-5000, g43406
military specification 4th material response or mil-s-6098, g87350 military specification 5th material response or mil-s-6049 military
specification 6th material response or ams6322, g87400 assn standard 6th material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, class 2 federal specification all treatment responses
Specification Data:
80205-nas1054 professional/industrial association standard and 80205-nas178/canceled/ professional/industrial association standard and
73197-hs48 manufacturers standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A528u0
Mil-std (military Standard):
Mil-s-8695 spec.