

View Online at <https://aerobasegroup.com/nsn/5320-00-262-7802>

**Fastener Length:**

Between 1.571 inches and 1.591 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.068 inches and 0.078 inches

**Shank Diameter:**

Between 0.310 inches and 0.312 inches

**Shank Style:**

Err-090

**Head Major Diameter:**

Between 0.475 inches and 0.505 inches

**Grip Length:**

Between 1.313 inches and 1.375 inches

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Material:**

Steel comp 4037 or steel comp 4130 or steel comp 4140 or steel comp 4340 or steel comp 8735 or steel comp 8740

**Material Specification:**

Mil-s-8695, g40370 military specification 1st material response or mil-s-6758, g41300 military specification 2nd material response or mil-s-5626 military specification 3rd material response or ams6382, g41400 assn standard 3rd material response or mil-s-5000, g43406 military specification 4th material response or mil-s-6098, g87350 military specification 5th material response or mil-s-6049 military specification 6th material response or ams6322, g87400 assn standard 6th material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, class 2 federal specification all treatment responses

**Specification Data:**

80205-nas1054 professional/industrial association standard and 80205-nas178/canceled/ professional/industrial association standard and 73197-hs48 manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-8695 spec.