

View Online at <https://aerobasegroup.com/nsn/5320-00-264-4469>

**Fastener Length:**

Between 0.615 inches and 0.635 inches

**Head Style:**

Undersized oval countersunk

**Head Height:**

Between 0.003 inches and 0.005 inches

**Shank Diameter:**

Between 0.155 inches and 0.158 inches

**Shank Style:**

Straight

**Head Major Diameter:**

Between 0.240 inches and 0.247 inches

**Head Minor Diameter:**

Between 0.185 inches and 0.195 inches

**Countersink Height:**

0.037 inches

**Grip Length:**

0.391 inches

**Shear Strength:**

26000 single pounds per square inch

**Countersink Angle:**

Between 99.5 degrees and 100.5 degrees

**Material:**

Aluminum alloy 2117

**Material Specification:**

Qq-a-430 federal specification single material response

**Surface Treatment:**

Anodize or oxide film

**Surface Treatment Specification:**

Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response

**Specification Data:**

80205-nas1097 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-a-8625 spec.