

View Online at <https://aerobasegroup.com/nsn/5320-00-271-7324>

Fastener Length:

Between 0.240 inches and 0.260 inches

Head Style:

Undersized oval countersunk

Head Height:

Between 0.003 inches and 0.005 inches

Shank Diameter:

Between 0.093 inches and 0.096 inches

Shank Style:

Straight

Head Major Diameter:

Between 0.126 inches and 0.1478 inches

Head Minor Diameter:

Between 0.086 inches and 0.096 inches

Countersink Height:

0.021 inches

Grip Length:

Between 0.099 inches and 0.119 inches

Shear Strength:

24000 single pounds per square inch

Countersink Angle:

Between 99.5 degrees and 100.5 degrees

Heat Treatment:

H-32 strain hardened

Material:

Aluminum alloy 5056

Material Specification:

Qq-a-430 federal specification single material response

Surface Treatment:

Anodize or oxide film

Surface Treatment Specification:

Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response

Specification Data:

80205-nas1097 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.