## NSN 5320-00-279-4668

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-00-279-4668



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

### Fastener Length:

Between 2.240 inches and 2.265 inches

#### Head Style:

Err-090

#### **Head Height:**

Between 0.165 inches and 0.177 inches

#### Shank Diameter:

0.422 inches

#### Shank Style:

Pin-rivet, tapered, threaded

#### Head Major Diameter:

Between 0.672 inches and 0.686 inches

#### Tip Diameter:

0.389 inches

## Lubrication:

Cetyl alcohol

#### Grip Length:

Between 1.677 inches and 1.692 inches

#### Thready Qty Per Inch (tpi):

24

#### **Thread Size:**

0.375 inches

#### Material:

Steel comp 8740 or steel comp 4340

#### Material Specification:

Mil-s-6049 military specification 1st material response or mil-s-5000 military specification 2nd material response

#### Surface Treatment:

Cadmium

#### Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

#### **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5320-00-279-4668

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

Mil-std (military Standard):

Mil-s-6049 spec.

