## NSN 5320-00-279-4672

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-279-4672 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: 1.156 inches **Head Style:** Flush countersunk **Shank Diameter:** 0.3144 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** Between 0.520 inches and 0.577 inches Tip Diameter: 0.304 inches Lubrication: Cetyl alcohol **Grip Length:** 0.750 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Countersink Angle:** 100.0 degrees Material: Steel comp 8740 or steel comp e4340 or steel comp 4340 **Material Specification:** Mil-s-6049 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-5000 military specification 3rd material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

No

Demilitarization:

## NSN 5320-00-279-4672

Pin-rivet - Page 2 of 2



Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6049 spec.