## NSN 5320-00-286-0685

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-286-0685 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.760 inches and 0.785 inches **Head Style:** Err-090 **Head Height:** Between 0.058 inches and 0.070 inches **Shank Diameter:** 0.2636 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** Between 0.379 inches and 0.389 inches Tip Diameter: 0.2564 inches Lubrication: Cetyl alcohol and dry film **Grip Length:** Between 0.427 inches and 0.442 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.250 inches **Shear Strength:** 95000 single pounds per square inch Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1728 professional/industrial association standard Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5320-00-286-0685

Pin-rivet - Page 2 of 2



em			

No

Fiig:

A528u0