# NSN 5320-00-286-4244

Pin-rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-286-4244

## Head Style:

Flush countersunk

## Shank Diameter:

Between 0.1880 inches and 0.1895 inches

# Shank Style:

Stump

## Head Major Diameter:

Between 0.344 inches and 0.386 inches

#### Lubrication:

Cetyl alcohol

## Grip Length:

Between 0.845 inches and 0.906 inches

## Min. Tensile Strength (psi):

160000 pounds per square inch

## Hardness Rating:

77.0 rockwell superficial 45-n and 82.0 rockwell superficial 45-n

## Shear Strength:

95000 single pounds per square inch

# **Countersink Angle:**

100.0 degrees

# Material:

Steel comp 8740 or steel comp 4340 or steel comp 4140

# Material Specification:

Astm a547 grades 87404340 or 4140 assn standard all material responses

## Surface Treatment:

Cadmium

# Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

## **Specification Data:**

80205-nas148 professional/industrial association standard

## Shelf Life:

N/a

# Unit Of Measure:

--

## Demilitarization:

No

# Fiig:

A528u0