# NSN 5320-00-288-3319

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-288-3319

**Thread Class:** 

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

0.770 inches

# Head Style:

Flush countersunk

#### Shank Diameter:

0.2624 inches

#### Shank Style:

Pin-rivet, tapered, threaded

#### Head Major Diameter:

0.413 inches

# Tip Diameter:

0.2564 inches

# Lubrication:

Cetyl alcohol and dry film

# Grip Length:

0.437 inches

# Thready Qty Per Inch (tpi):

28

# Min. Tensile Strength (psi):

125000 pounds per square inch

#### **Thread Size:**

0.250 inches

#### Shear Strength:

220000 single pounds per square inch

#### Countersink Angle:

100.0 degrees

#### Material:

Steel comp xm-13

#### Material Specification:

Ams 5629 assn standard single material response

#### Surface Treatment:

Passivate

# Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

## Thread Series Designator:

Unjf

### Shelf Life:

N/a

# NSN 5320-00-288-3319

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

