NSN 5320-00-288-3320



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-00-288-3320 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: 0.756 inches **Head Style:** Flush countersunk **Shank Diameter:** 0.3260 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** 0.494 inches Tip Diameter: 0.3215 inches Lubrication: Cetyl alcohol and dry film **Grip Length:** 0.375 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 125000 pounds per square inch **Thread Size:** 0.312 inches **Shear Strength:** 220000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response

Thread Series Designator: Unjf

Shelf Life:

N/a

NSN 5320-00-288-3320

Pin-rivet - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A528u0