NSN 5320-00-288-3484

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-288-3484

Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
0.582 inches
Head Style:
Err-090
Head Height:
Between 0.058 inches and 0.070 inches
Shank Diameter:
0.2636 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.379 inches and 0.389 inches
Hole Depth:
0.2603 inches
Lubrication:
Cetyl alcohol
Grip Length:
0.250 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
220000 pounds per square inch
Thread Size:
0.250 inches
Shear Strength:
125000 single pounds per square inch
Material:
Steel comp xm-13
Material Specification:
Ams 5629 assn standard 1st material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1728 professional/industrial association standard

NSN 5320-00-288-3484

Pin-rivet - Page 2 of 2



_						
C	he	14		iŧ	0	•
J			_		ㄷ	-

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0