NSN 5320-00-288-3489

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-288-3489 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: 0.832 inches **Head Style:** Err-090 **Head Height:** Between 0.068 inches and 0.080 inches Shank Style: Pin-rivet, tapered, threaded **Head Major Diameter:** Between 0.379 inches and 0.389 inches Tip Diameter: 0.2636 inches Lubrication: Cetyl alcohol **Grip Length:** 0.500 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch **Thread Size:** 0.250 inches **Shear Strength:** 125000 single pounds per square inch Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard 1st material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas1728 professional/industrial association standard

Shelf Life:

N/a

NSN 5320-00-288-3489

Pin-rivet - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A528u0