

View Online at <https://aerobasegroup.com/nsn/5320-00-288-3608>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.437 inches and 0.457 inches

Head Style:

Err-090

Head Height:

Between 0.037 inches and 0.047 inches

Width Between Flats:

Between 0.079 inches and 0.080 inches

Shank Diameter:

Between 0.1630 inches and 0.1635 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.242 inches and 0.262 inches

Lubrication:

Cetyl alcohol

End Application:

Aircraft, hercules c-130, aircraft, eagle f-15 helicopter observation (ahip), oh-58d, aircraft, galaxy c-5, joint stars target, aircraft, harrier av-8b, aircraft, sof (ac-130h, mc-130h, ec-130e, hc-130), aircraft, hornet f/a-18, aircraft, phantom f-4, aircraft, f-16

Grip Length:

0.130 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.164 inches

Shear Strength:

95000 single pounds per square inch

Material:

Iron alloy 660

Material Specification:

Ams 5731 assn standard 1st material response

Surface Treatment:

Passivate

Surface Treatment Specification:

258, fscm 73197 mfr ref single treatment response

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0