NSN 5320-00-288-3737

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-288-3737 **Thread Class:** За **Thread Direction:** Right-hand **Fastener Length:** Between 0.723 inches and 0.743 inches **Head Style:** Err-090 **Head Height:** Between 0.078 inches and 0.088 inches Width Between Flats: Between 0.158 inches and 0.162 inches **Shank Diameter:** Between 0.3740 inches and 0.3745 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.565 inches and 0.600 inches Lubrication: Cetyl alcohol **End Application:** Wsd: aircraft, eagle f-15; aircraft, hornet f/a-18 **Grip Length:** 0.193 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.375 inches **Shear Strength:** 125000 single pounds per square inch

Criticality Code Justification:

Special Features:

Weapon system essential

Material:

Steel comp xm-13

Material Specification:

Ms 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

258, fscm 73197 mfr ref single treatment response

NSN 5320-00-288-3737

Pin-rivet - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A528u0