# NSN 5320-00-291-5516

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-00-291-5516



## **Thread Class:**

3a

**Thread Direction:** 

Right-hand

# Fastener Length:

Between 2.411 inches and 2.436 inches

# Head Style:

Err-090

## Head Height:

Between 0.141 inches and 0.153 inches

# Shank Diameter:

0.3403 inches

# Shank Style:

Pin-rivet, tapered, threaded

# Head Major Diameter:

Between 0.579 inches and 0.591 inches

### Tip Diameter:

0.3319 inches

## Lubrication:

Cetyl alcohol

## Grip Length:

Between 1.927 inches and 1.942 inches

## Thready Qty Per Inch (tpi):

24

## Thread Size:

0.312 inches

### Shear Strength:

108000 single pounds per square inch

## Material:

Steel comp 8740 or steel comp e4340

### **Material Specification:**

Mil-s-6049 military specification 1st material response or mil-I-s-5000 military specification 2nd material response

### Surface Treatment:

Cadmium and chromate and chromate

### Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

## **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5320-00-291-5516

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6049 spec.

