NSN 5320-00-292-6069



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-00-292-6069 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.740 inches and 0.760 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.079 inches and 0.080 inches **Shank Diameter:** Between 0.1630 inches and 0.1635 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.256 inches and 0.261 inches Lubrication: Cetyl alcohol **End Application:** Wsd: aircraft, eagle f-15; aircraft, hornet f/a-18 **Grip Length:** 0.443 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.164 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** 100.0 degrees **Criticality Code Justification: Special Features:** Weapon system essential Material: Iron alloy 660 **Material Specification:**

Ams 5737 assn standard single material response or ams 5731 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

258, fscm 73197 mfr ref single treatment response

NSN 5320-00-292-6069

Pin-rivet - Page 2 of 2



| Thread Series Designator: |
|---------------------------|
| Unjc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A528u0