NSN 5320-00-292-6094



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-00-292-6094 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.165 inches and 1.185 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.095 inches and 0.097 inches **Shank Diameter:** Between 0.2646 inches and 0.2651 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.390 inches and 0.395 inches Lubrication: Cetyl alcohol **Grip Length:** 0.755 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Shear Strength:** 10490 double pounds per square inch **Countersink Angle:** 100.0 degrees Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response or ams 5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** 258, fscm 73197 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5320-00-292-6094

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0