NSN 5320-00-298-5105

Blind Rivet - Page 1 of 1

Mil-s-7720 spec.



| View Online at https://aerobasegroup.com/nsn/5320-00-298-5105 |
|--|
| Fastener Length: |
| Between 0.223 inches and 0.243 inches |
| Head Style: |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) |
| Shank Diameter: |
| Between 0.189 inches and 0.192 inches |
| Shank Style: |
| Self-plugging shank w/grooved end for locking |
| Head Major Diameter: |
| 0.305 inches |
| Expansion Device: |
| Drive stem-type h |
| Grip Length: |
| Between 0.166 inches and 0.227 inches |
| Shear Strength: |
| 75000 single pounds per square inch |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Material: |
| Steel comp 416 stem |
| Material Specification: |
| Qq-s-763 federal specification single material response stem |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Qq-p-416, type 1, cl 3 federal specification single treatment response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A040a0 |
| Mil-std (military Standard): |