NSN 5320-00-303-1059

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-303-1059 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.500 inches and 0.525 inches **Head Style:** Err-090 **Head Height:** Between 0.032 inches and 0.042 inches **Shank Diameter:** 0.169 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.264 inches and 0.278 inches **Grip Length:** 0.250 inches **Thread Size:** 0.164 inches **Shear Strength:** 108000 single pounds per square inch **Special Features:** 0.172 in. Second shank dia, and lubrication cetyl alcohol Material: Steel comp e4340 or steel comp 4340 or steel comp 8740 **Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

Fiig: A528u0

No

Demilitarization:

NSN 5320-00-303-1059

Pin-rivet - Page 2 of 2



Mil-std (military Standard):

Mil-s-5000 spec.