# NSN 5320-00-303-1069

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-00-303-1069



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

### Fastener Length:

Between 0.552 inches and 0.572 inches

#### Head Style:

Flush countersunk

#### Width Between Flats:

Between 0.079 inches and 0.080 inches

#### Shank Diameter:

Between 0.1630 inches and 0.1635 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.326 inches and 0.330 inches

#### Lubrication:

Cetyl alcohol

# Grip Length:

0.250 inches

#### Thready Qty Per Inch (tpi):

36

#### Min. Tensile Strength (psi):

160000 pounds per square inch

#### **Thread Size:**

0.164 inches

#### Shear Strength:

95000 single pounds per square inch

#### Countersink Angle:

100.0 degrees

#### Material:

Titanium alloy

#### Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### Thread Series Designator:

Unjc

# Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5320-00-303-1069

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

