
## NSN 5320-00-304-9577

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

#### Fastener Length:

Between 0.865 inches and 0.885 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.098 inches and 0.112 inches

#### Width Between Flats:

Between 0.127 inches and 0.130 inches

#### Shank Diameter:

Between 0.3115 inches and 0.3120 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.472 inches and 0.502 inches

#### Lubrication:

Cetyl alcohol

## Grip Length:

0.380 inches

## Thready Qty Per Inch (tpi):

24

## Min. Tensile Strength (psi):

160000 pounds per square inch

#### Thread Size:

0.312 inches

## Shear Strength:

95000 single pounds per square inch

#### Material:

Iron alloy 660

## Material Specification:

Ams 5731 assn standard single material response or ams 5737 assn standard single material response

## Surface Treatment:

Passivate

## Surface Treatment Specification:

258, fscm 73197 mfr ref single treatment response

## Thread Series Designator:

Unjf

## Shelf Life:

N/a

# NSN 5320-00-304-9577

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

