NSN 5320-00-317-1470



Blind Rivet - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5320-00-317-1470 **Head Style:** Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) **Shank Diameter:** Between 0.213 inches and 0.215 inches **Shank Style:** Threaded self-plugging shank w/sleeve **Head Major Diameter:** 0.385 inches **Expansion Device:** Threaded stem **Grip Length:** Between 0.407 inches and 0.469 inches **Hardness Rating:** 39.0 rockwell c nut and 43.0 rockwell c nut **Countersink Angle:** 100.0 degrees **Special Features:** Self-locking Material: Steel comp 304 sleeve or steel comp 303f sleeve or steel comp 303 sleeve **Material Specification:** Mil-s-5626 military specification 1st material response bolt or mil-s-6049 military specification 2nd material response bolt or mil-s-6758 military specification 3rd material response bolt **Surface Treatment:** Cadmium sleeve and chromate sleeve and passivate sleeve **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response nut **Specification Data:** 80205-nas1750 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

ı ııg.

A040a0

Mil-std (military Standard):

Mil-s-5626 spec.