NSN 5320-00-317-1474

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-317-1474

Head :	Style:
--------	--------

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.213 inches and 0.215 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Head Major Diameter:

Between 0.342 inches and 0.385 inches

Expansion Device:

Threaded stem

Grip Length:

Between 0.470 inches and 0.531 inches

Hardness Rating:

39.0 rockwell c and 43.0 rockwell c nut

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp 4140 or steel comp 8740 or steel comp 4130 nut

Material Specification:

Qq-s-763 federal specification 1st material response or ams 5639 assn standard 1st material response or ams 5641 assn standard 2nd material response or astm a582 assn standard 3rd material response sleeve

Surface Treatment:

Cadmium and chromate nut

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification 1st treatment response and qq-p-35 federal specification 2nd treatment response sleeve

Specification Data:

80205-nas1750 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-5626 spec.