NSN 5320-00-318-9148

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-318-9148

Head	Ctvi	

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.213 inches and 0.215 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Head Major Diameter:

Between 0.342 inches and 0.385 inches

Expansion Device:

Threaded stem

Grip Length:

Between 0.282 inches and 0.344 inches

Hardness Rating:

39.0 rockwell c nut and 43.0 rockwell c nut

Countersink Angle:

100.0 degrees

Material:

Steel comp 4140 nut or steel comp 8740 nut or steel comp 4130 nut

Material Specification:

Qq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 1st material response sleeve or ams 5641 assn standard 2nd material response sleeve or astm a582 assn standard 3rd material response sleeve

Surface Treatment:

Cadmium sleeve and chromate sleeve and passivate sleeve

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response nut

Specification Data:

80205-nas1750 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-5626 spec.