

View Online at <https://aerobasegroup.com/nsn/5320-00-322-0174>

**Fastener Length:**

Between 2.015 inches and 2.025 inches

**Head Style:**

Flush countersunk

**Shank Diameter:**

Between 0.311 inches and 0.312 inches

**Shank Style:**

Stump

**Head Major Diameter:**

Between 0.416 inches and 0.479 inches

**Lubrication:**

Cetyl alcohol

**Grip Length:**

Between 1.689 inches and 1.750 inches

**Features Provided:**

Casehardened

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

76.1 rockwell superficial 15-n and 80.9 rockwell superficial 15-n

**Shear Strength:**

14600 double pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Steel comp 4037 or steel comp 4140 or steel comp 8740

**Material Specification:**

Astm a547 assn standard all material responses

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Specification Data:**

80205-nas1420 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0